

SECTION 9.36 TRADE-OFF CALCULATION HELPER for construction in accordance with ABC2014:B:9.36.2.11

TRADE-OFF COMPLIES WHEN SUM OF PROPOSED 'A / Rp' VALUES IS NO GREATER THAN SUM OF REFERENCE 'A / Rr' VALUES

For ABOVE-GROUND OPAQUE ASSEMBLIES TRADE-OFF:

DOES TRADE-OFF COMPLY?

Locate the effective thermal resistance "ETR" (RSI) for the assembly inTable 9.36.2.6.A. (No HRV in building) or 9.36.2.6.B (with HRV)

"ETR" reduction must result in any wall or joist-type roof assembly no less than 55% of RSI per 9.36.2.6.A. or B., if applicable

"ETR" reduction must result in floor over unheated space, or non-joist-type roof no less than 60% of RSI per 9.36.2.6.A. or B., if applicable

Assemblies with embedded heating cables, pipes or membranes may not be traded under 9.36.2.11.

RECERENCE ASSEMBLY

31,5253

DRODOSED ASSEMBLY

	Assembly type and location	Roof/wall/floor Area A (sq.m.)	ETR RSI Reference Rr	A) Rr	ETR RSI Proposed Rp	Proposed A / Rp
1	Walls (Typ.)	64	2.97	21.39	3.10	20.50
2	Tall Walls	30	2.97	10.13	2.81	10.71
3						
4						

Yes